

Sonance Symphony® Series Symphony S622_C Cabinet Speaker



Sonance Symphony® Cabinet Speakers

The Sonance Symphony® S622_C Cabinet speaker offers the performance and quality of Sonance Symphony series in-wall speakers to those who can't use in-wall speakers. Ideal for both multi-channel home theater and stereo music applications, Symphony S622_C Cabinet speakers deliver impressive musical performance, yet they integrate into a wide variety of lifestyles.

The new enclosure is one key to the Symphony S622_C Cabinet speaker's superior performance. The 1"-thick MDF baffle and back panels maintain ultra-high rigidity and banish resonances. An exclusive laminate made-up of ½" MDF and ½" particle board maximizes stiffness and reduces resonances in the top, bottom and side panels.

The Sonance Symphony S622_C Cabinet speaker brings high-quality entertainment to life anywhere in the home while its compact size allows it to be used in a variety of installations.

Features:

- Cabinet design offers Sonance Symphony series quality and performance to listeners who can't use in-wall speakers.
- Same voicing as Sonance Symphony in-wall speakers allows mix-and-match between in-wall and cabinet versions while maintaining character and quality of 'Sonance sound'.
- Polypropylene woofer cone delivers robust, low-distortion bass; silk dome tweeter has extended high-frequency response.
- Tweeter acoustic back chamber widens and smoothes high-frequency performance.
- Large woofer magnet increases output and power handling.
- Ultra-rigid 1" MDF baffle and back panels minimize resonances.
- Cabinet top, bottom & sides made from an exclusive laminate of ½" MDF and ½" particle board, for superior stiffness and resonance damping.
- Large connection terminals accept up to 14AWG speaker wire.
- Compact size increases installation options.



www.sonance.com

212 Avenida Fabricante
San Clemente, CA 92672-7531 USA
(800) 582-7777 or (949) 492-7777
FAX: (949) 361-5151
Technical Support: (800) 582-0772

SPECIFICATIONS

Sonance Symphony S622_C Cabinet

Tweeter	1" (25mm) Silk dome, Ferrofluid-cooled
Woofer	6½" (165mm) Polypropylene cone, rubber surround
Frequency Response	45Hz – 20kHz ±3dB
Impedance	8 Ohms nominal; 6 Ohms minimum
Power Handling	5 watts minimum; 125 Watts maximum
Sensitivity	89dB SPL (2.83V 1 meter)
Baffle & Back Panel Material	1" MDF
Top, Bottom & Side Panel Material	Laminate (½" MDF / ½" particle board)
Grille Material	Black cloth
Dimensions (W x H x D)	7½" (310mm) x 11" (206mm) x 11½" (98mm)
Shipping Weight	18 lbs. (8.2 KG) each

DIMENSIONS

Sonance Symphony S622_C Cabinet Speaker

